 **Medium Duty:**
Incidental,
Non-deliberate Traffic

For use in non-vehicular traffic situations only.

Actual load rating is determined by the box and cover combination.

Weights and dimensions may vary slightly.

Cover comes standard with permanent markings for manufacturer, load rating, model size and manufacturing location.

Revision 4/2018

©2018 Oldcastle, Inc.

OPTIONS

AVAILABLE PLASTIC COVERS:

H2O Plastic Cover (for use with cast iron frame)

AVAILABLE MONITOR SET:

Cast Iron Cover with Cast Iron Frame (2 Piece)
(Requires use of Expander Ring)

LOCKING OPTIONS FOR ALL COVERS:

Penta Nut (Small or Large)

ADD ON OPTIONS FOR ALL COVERS:

Touch Read Hole




H2O Plastic



Cast Iron Cover



Cast Iron Frame



Penta Nut Detail

RAW MATERIAL SPECIFICATIONS

- Meter Boxes are Polyethylene Blend
- Vertical load rating minimum 20,000 lbs
- Sidewall loading of 200 lb side load, applied with a 4" X 4" plate
- Multi-layer wall construction
- Black exterior surface to provide UV protection
- Gray foaming for strength and insulating value
- White interior surface for ease of meter reading
- Manufactured by Oldcastle Precast Enclosure Solutions

CAST IRON METER RING AND LID SPECIFICATIONS

- Made of cast iron conforming to ASTM A48 standards and marked with country of origin
- Coated with a factory applied water based asphalt paint
- Castings are ground smooth and cleaned by shot blasting, uniform quality, free from sand holes, shrinkage, cracks and other surface defects, with a dimensional tolerance of +/- 1/16" per foot based on the accepted foundry tolerances outlined in the Iron Castings Handbook published by the American Foundry Society.

PRODUCT LOAD RATING



Medium Duty: Incidental, Non-deliberate Traffic

For use in non-vehicular traffic situations only. Actual load rating is determined by the box and cover combination.

NOTES

Actual load rating is determined by the box and cover combination.
Weights and dimensions may vary slightly