



Notes:

- Precast concrete structure shall be manufactured in accordance with ASTM Designation C857 and C858.
- Perk Filter[™] Catch basin shall be supplied with traffic rated (H20) bicycle-proof grates and solid plate cover.
- Inlet pipe(s) may enter device on three sides of the inlet chamber. Outlet pipe(s) may exit on all four sides. All pipe is Ø 12" maximum.
- Inlet chamber shall be supplied with a drain-down device designed to remove standing water between storm events.
- Perk Filter[™] cartridge shall be maintained in accordance with manufacturer recommendations.
- 6. For depths less than the specified minimum contact Oldcastle[®] Stormwater Solutions for engineering assistance.







Perk Filter™

Concrete Catch Basin

Single Cartridge



Oldcastle® Stormwater Solutions

7921 Southpark Plaza, Suite 200 | Littleton, CO | 80120 | Ph: 800.579.8819 | oldcastlestormwater.com

THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE PRECAST, INC. IT IS SUBMITTED FOR REFERENCE PURPOSES ONLY AND SHALL NOT BE USED IN ANY WAY INJURIOUS TO THE INTERESTS OF SAID COMPANY, COPYRIGHT © 2014 OLDCASTLE PRECAST, INC. ALL RIGHTS RESERVED

DRAWING NO. PF-CCB-0001 J ECO ECO-0144 JPR 6/4/08 SHEET 1 OF 1