

48" DRYWELL MANHOLE

FRAME AND COVER

3" = 275 lbs.
7" = 350 lbs.

GRADE RING

2" = 80 lbs.
3" = 125 lbs.
4" = 165 lbs.
6" = 245 lbs.
12" = 490 lbs.

ECCENTRIC CONE

2,480 lbs.

Lift Pin or Hole
(2 Places Typ.)

DRYWELL RISER

Height	Weight
5'-0"	4,060 lbs.

Perforated Section
w/2 $\frac{3}{8}$ " $\varnothing$ Holes
14 Columns 8 Rows

DRYWELL BASE

Height	Weight
5'-0"	5,390 lbs.

Perforated Section
w/2 $\frac{3}{8}$ " $\varnothing$ Holes
14 Columns 8 Rows

3" (Suburban) or 7" (Standard)

Lift Loop
(3 Places)

FLAT TOP

(Other Hole Sizes and Configurations Available)
1,650 lbs.

CONCENTRIC CONE

2,080 lbs.

JOINT DETAIL

Notes:

- Manholes per Specification: ASTM C478
- Rubber Gasket: ASTM C443
- Holes: Cored as Required.
- Frame & Cover: Gray Cast Iron ASTM A48 Class 30, Watertight/Tamperproof Cover Available.
- Optional Extended Base Available.



Oldcastle Precast®

PO Box 323, Wilsonville, Oregon 97070-0323
Tel: (503) 682-2844 Fax: (503) 682-2657

48" DRYWELL MANHOLE

File Name: 020-48MH-D

Issue Date: 2018

oldcastleprecast.com/wilsonville

48" DRYWELL MANHOLE