



**V-1600-3**  
**Frame & Cover (2)**  
 (With Oldcastle Logo)

**Top GI**  
**6'-0"x15'-0"x2'-6"x7"W**  
 Weight - 19,290 Lbs.

**Baffle GI**  
**6'-2"x9'-2"x5"W**  
 Weight - 3,600 Lbs.

**Extension GI (2)**  
**6'-0"x15'-0"x2'-0"x7"W**  
 Weight - 7,760 Lbs.

**Extension GI (2)**  
**6'-0"x15'-0"x2'-6"x7"W**  
 Weight - 9,700 Lbs.

**Base GI**  
**6'-0"x15'-0"x2'-6"x7"W**  
 Weight - 19,840 Lbs.

**SPECIFICATIONS:**

1. Concrete: Design Strength of 5500 PSI at 28 Days.
2. Steel Reinforcement: ASTM A-615 Grade 60.
3. Loading: Designed for HS-20 Loading.
4. C.I. Castings: ASTM A-48 Class 30/35.

**GENERAL NOTES:**

1. Interceptor is Structurally and Hydraulically Engineered Conforming to Uniform Plumbing Code.
2. Liquid Capacity is 5,570 Gallons with Solids Retention Capacity of Approx. 21,692 Pounds.
3. Recommended for Flow Rate up to 90 GAL Per Minute.