

Ring & Cover :

*Note: Varies Per Customer Specs

35" x 3" Grade Ring

Weight : 145 Lbs.

24" x 3" Grade Ring

Weight : 105 Lbs.

48" Dia. Flat Slab

Weight : Varies

Flat Slab	
Access	Weight (Lbs.)
24"	1,770
35"	1,700

48" Dia. Conc. Cone

Weight : Varies

Cone	
Access	Weight (Lbs.)
24"	1,550
35"	1,530

48" Dia. Risers

Weight : See Chart

Riser	
B	Weight (Lbs.)
12"	830
24"	1,700
36"	2,535
48"	3,485

48" Dia. Base

Weight : See Chart

** Weights do not include invert

Base	
A	Weight (Lbs.)
38"	**4,749
48"	**5,525

Extended Base	
A	Weight (Lbs.)
38"	**5,352
48"	**6,785

GENERAL NOTES:

1. Manhole Walls, Transition Slabs, Cones, Tops, and Base Sections Meet or Exceed the Requirements of ASTM C-478.
2. Joint Connections to be Gaskets Conforming to ASTM C-443 Requirements.
3. Resilient Connectors to be Boots Conforming to ASTM C-923 Requirements
4. Following Coatings available upon request: (Thane-Coat, Bitumastic, Tnemec)

