

Ring & Cover :

*Note: Varies Per Customer Specs

35" x 3" Grade Ring

Weight : 145 Lbs.

24" x 3" Grade Ring

Weight : 105 Lbs.

48" Dia. Conc Cone

Weight : Varies

Cone	
Access	Weight (Lbs.)
24"	1,550
35"	1,530

60" Dia. Flat Slab

Weight : Varies

Flat Slab	
Access	Weight (Lbs.)
24"	2,550
35"	2,535

60" Dia. Risers

Weight : See Chart

Riser	
B	Weight (Lbs.)
12"	1,009
24"	2,012
36"	3,018
48"	4,025

60" Dia. Bases

Weight : See Chart

Ext. Base	
A	Weight (Lbs.)
20"	**5,368
26"	**5,880
32"	**6,401
38"	**6,918
44"	**7,438
50"	**7,951
56"	**8,476
62"	**8,988
68"	**9,509

GENERAL NOTES:

1. Manhole Walls, Transition Slabs, Cones, Tops, and Base Sections Meet or Exceed the Requirements of ASTM C-478.
2. Joint Connections to be Gaskets Conforming to ASTM C-443 Requirements.
3. Resilient Connectors to be Boots Conforming to ASTM C-923 Requirements
4. Following Coatings available upon request: (Thane-Coat, Bitumastic, Tnemec)

