

Ring & Cover :

*Note: Varies Per Plan details and Specs

35" x 3" Grade Ring

Weight : 145 Lbs.

24" x 3" Grade Ring

Weight : 105 Lbs.

48" Dia. Conc Cone

Weight : Varies

| Cone | |
|--------|---------------|
| Access | Weight (Lbs.) |
| 24" | 1,550 |
| 35" | 1,530 |

72" Dia. Flat Slab

Weight : Varies

| Flat Slab | |
|-----------|---------------|
| Access | Weight (Lbs.) |
| 24" | 3,360 |
| 35" | 3,335 |

72" Dia. Risers

Weight : See Chart

| Riser | |
|-------|---------------|
| B | Weight (Lbs.) |
| 12" | 1,761 |
| 24" | 3,518 |
| 36" | 5,280 |
| 48" | 7,041 |

72" Dia. Bases

Weight : See Chart

** Weights do not include invert

| Ext. Base | |
|-----------|---------------|
| A | Weight (Lbs.) |
| 12" | **6,939 |
| 18" | **7,818 |
| 24" | **8,700 |
| 30" | **9,579 |
| 36" | **10,458 |
| 42" | **11,340 |
| 48" | **12,219 |
| 54" | **12,490 |
| 60" | **12,490 |

GENERAL NOTES:

1. Manhole Walls, Transition Slabs, Cones, Tops, and Base Sections Meet or Exceed the Requirements of ASTM C-478.
2. Joint Connections to be Gaskets Conforming to ASTM C-443 Requirements.
3. Resilient Connectors to be Boots Conforming to ASTM C-923 Requirements
4. Following Coatings available upon request: (Thane-Coat, Bitumastic, Tnemec)

