

### Ring & Cover :

\*Note: Varies Per Customer Specs

#### 35" x 3" Grade Ring

Weight : 145 Lbs.

#### 24" x 3" Grade Ring

Weight : 105 Lbs.

#### 48" Dia. Conc Cone

Weight : Varies

Cone	
Access	Weight (Lbs.)
24"	2,429
35"	1,429

#### 60" Dia. Flat Slab

Weight : Varies

Flat Slab	
Access	Weight (Lbs.)
24"	3,644
35"	3,075

#### 60" Dia. Risers

Weight : See Chart

Riser	
A	Weight (Lbs.)
12"	1,009
24"	2,012
36"	3,018
48"	4,025
60"	5,173

#### 60" Dia. Bases

Weight : See Chart

Ext. Base	
A	Weight (Lbs.)
20"	5,368
26"	5,880
32"	6,401
38"	6,918
44"	7,438
50"	7,951
56"	8,476
62"	8,988
68"	9,509

### GENERAL NOTES:

1. Manhole Walls, Transition Slabs, Cones, Tops, and Base Sections Meet or Exceed the Requirements of ASTM C-478.
2. Joint Connections to be Gaskets Conforming to ASTM C-443 Requirements.
3. Resilient Connectors to be Boots Conforming to ASTM C-923 Requirements
4. Following Coatings available upon request: (T-Coat, Bitumastic, Tnemec)

