

Carson® HDPE Enclosures are lightweight, easy to install, and provide strong, durable performance with water and chemical resistance.





Cover: HDPE

A. HDPE Cover


- T-Cover or Flush Cover option. T-cover lid seal prevents material from entering body.
- Patented Hinge lid available on some models.
- · Custom coloring available.
- Hardware free Drop-N-Lock[™] system. No nuts or bolts required!
- EZ Lock self cleaning hardware. Eliminates seizing bolts.
- Standard Hex or Penta head hardware.

B. Reinforced Sidewall Design

- Truss-T series has bridge truss' added to sections as required to maximize strength.
- Eliminates sidewall flex to ensure cover/body integrity. Available loop brace on some sizes.

C. Flared Side Wall Design

• Maximizes internal volume. Up to 40% more work or storage space versus straight wall designs.







Material	Model	Size (LxW)	Shape	Wall Type	Depths	Design Load	Tier
HDPE	708	6" Dia	0	Flared 🔼	9"		
	809	6" Dia	0		9"		
	0011	10" Dia	0		10"		
	0012	14" x 20"			6" 12" 18"		
	910	9" Dia	0		10" 18"		
	1015	10" x 15"			6" 12" <mark>18"</mark>		
	1017	13" x 19"		Straight	12"		
	1419	10" x 15"		Flared $igsqcut igsqcut igs$	3" 6" <mark>9"</mark> 12" 15" 24"		Ped
	1520	15" x 20"			18" <mark>24</mark> "		
	1220	12" x 20"			6" 12" <mark>18"</mark>	300 lb/ft²	
	1324	13" x 24"			12" <mark>14"</mark> 15" <mark>17"</mark>		
	1730	17" x 30"			12" 18" 24" <mark>36"</mark>		
	2200	12" Dia	0		18" <mark>24</mark> "		
	2424	24" x 24"			18" 24" 30" 36" 42" 48" *		
	2436	24" x 36"			18" 24" 30" 36" 42" 48" *		
	2448	24" x 48"			18" 24" 30" 36" 42" 48" *		
	2460	24" x 60"			18" 24" 30" 36" 42" 48" *		
	3636	36" x 36"			18" 24" 30" 36" 42" 48" *		
	3648	36" x 48"			18" 24" 30" 36" 42" 48" *		
	3660	36" x 60"			18" 24" 30" 36" 42" 48" *		

Actual load rating is determined by the box and cover combination.







Components and Options



Reinforced bottom edge helps the box retain its shape after compaction

Testing and Features









Resilient





Options



Resistant

Inside





Bottom



Flammable



Resistant



Conductive

877-250-5139 | OPI-Water@oldcastle.com

oldcastleprecast.com/enclosuresolutions