



SPECIFIER CHART

MODEL NO. STANDARD DEPTH	STANDARD & SHALLOW DEPTH (Data in these columns is the same for both STANDARD & SHALLOW versions)			STANDARD DEPTH -20 Inches-		MODEL NO. SHALLOW DEPTH	SHALLOW DEPTH -12 Inches-	
	INLET ID Inside Dimension (inch x inch)	GRATE OD Outside Dimension (inch x inch)	TOTAL BYPASS CAPACITY (cu. ft. / sec.)	SOLIDS STORAGE CAPACITY (cu. ft.)	FILTERED FLOW (cu. ft. / sec.)		SOLIDS STORAGE CAPACITY (cu. ft.)	FILTERED FLOW (cu. ft. / sec.)
FGP-1633FGO	16 X 33	18 X 36	7.0	2.5	1.7	FGP-1633FGO8	1.4	1.1
FGP-1836FGO	18 X 36	18 X 40	6.9	2.3	1.6	FGP-1836FGO8	1.3	.9
FGP-2234FGO	22 X 34	24 X 36	8.1	3.6	2.1	FGP-2234FGO8	2.1	1.4
FGP-2436FGO	24 X 36	24 X 40	8.0	3.4	2.0	FGP-2436FGO8	1.95	1.15
FGP-48FGO	48 X 48	20 X 54	6.3	2.2	1.5	FGP-48FGO8	1.25	.85

NOTES:

1. Filter insert shall have a high flow bypass feature.
2. Filter support frame shall be constructed from stainless steel Type 304.
3. Filter medium shall be *Fossil Rock™*, installed and maintained in accordance with manufacturer specifications.
4. Storage capacity reflects 80% of maximum solids collection prior to impeding filtering bypass.



Inlet Filtration

FloGard®
Catch Basin Insert Filter
Combination Inlet Style



Oldcastle®
Stormwater Solutions

7921 Southpark Plaza, Suite 200 | Littleton, CO | 80120 | Ph: 800.579.8819 | oldcastlestormwater.com
 THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE PRECAST, INC. IT IS SUBMITTED FOR REFERENCE PURPOSES ONLY AND SHALL NOT BE USED IN ANY WAY INJURIOUS TO THE INTERESTS OF SAID COMPANY. COPYRIGHT © 2010 OLDCASTLE PRECAST, INC. ALL RIGHTS RESERVED.

DRAWING NO. FGP-0004	REV A	ECO ECO-0127	DATE JPR 5/18/15	DATE JPR 1/25/13	SHEET 1 OF 1
-------------------------	----------	-----------------	---------------------	---------------------	--------------