



- NOTES:
1. CONCRETE: 28 DAY COMPRESSIVE STRENGTH F'C = 4,000 PSI.
 2. REINFORCING: ASTM A-615, GRADE 60.
 3. SUPPORTS AN H20 LOADING AS INDICATED BY AASHTO.
 4. CONTRACTOR TO VERIFY SIZE AND LOCATION OF ALL OPENINGS AND KNOCK-OUTS

KNOCK-OUTS, BLOCK-OUTS, TERMINATORS, AND CUSTOM LETTERING ON COVERS ARE AVAILABLE UPON REQUEST. CONTRACTOR MUST SPECIFY

STRUCTURE TYPE "60X60XVARIES VAULT"



Oldcastle™ Precast Inc.

690 WEST TAFT VINELAND RD. ORLANDO FL 32824
(407) 855-7580 • FAX: (407) 855-2424

CONTRACTOR PROJECT

DRAWN: SW	DATE: 2/9/07
CHECKED:	DATE:
PRODUCED:	SHIPPED:
STR. NO.: BOX #1	S.O. NO.: 00000
DRAWING NO.:	LN. NO.:
SCALE: 1"=4'	SHEET: 1 OF 1
LOC.:	

WALLS	PRODUCTION YARDAGE	WEIGHTS	REINFORCEMENT
	TOP:		
	WALL:		
	RISER:		
	RISER:		
	LIP:		
	CASTING:		
	HATCH:	4086170	42X60 TORSION F&C
	STEEL WT.:	---	
	CONC. WT.:		

REMARKS: