



NOTE:

- DESIGNED FOR ASHTO HS-20 LOADING.
- DESIGNED ACCORDING TO ASTM C507-07 AND ASTM C885-02.

NOTE:

SPECIAL ACCESS, GASTOOTS, KNOCKOUTS, PULLING EYES, TERMINATORS, RACKS, ETC. CAN BE PLACED AS SPECIFIED. SEE ACCESSORY DRAWINGS FOR MORE DETAIL.

CATALOG NUMBER	W	L	T	B	CORE TYPE	H	WEIGHT
UV2-2020	2'-0"	2'-0"	4"	4"	T	4'-0"	1,756
UV2-2030	2'-0"	3'-0"	4"	4"	T	4'-0"	2,168
ENGL-13/16	2'-2"	3'-4"	6"	6"	T	6'-0"	6,880
TRPL-13/16	2'-2"	10'-8"	6"	6"	C	6'-0"	15,170
DEL-13/16	2'-4"	7'-0"	6"	6"	C	4'-0"	11,951
UV2-3030	3'-0"	3'-0"	6"	6"	C	6'-0"	7,500
UV2-3050R	3'-0"	5'-0"	6"	6"	C	7'-0"	11,461
UV2-3050D	3'-0"	5'-8"	6"	6"	C	6'-0"	10,704
UV2-3010R	3'-0"	10'-0"	6"	6"	C	4'-4"	16,298
UV2-3010R	3'-0"	15'-0"	6"	6"	C	4'-4"	25,135
UV1-3434	3'-4"	3'-4"	4"	-	C	4'-0"	2,930
UV1-3470	3'-4"	7'-0"	4"	-	C	4'-0"	4,368
UV2-4040	4'-0"	4'-0"	6"	6"	C	6'-0"	8,276
UV2-4060	4'-0"	6'-0"	6"	6"	C	6'-0"	12,227
UV2-4080	4'-0"	8'-0"	6"	6"	C	6'-0"	16,178
UV2-4080	4'-0"	8'-0"	5"	5"	T	4'-0"	8,252
UV2-4011	4'-0"	11'-0"	6"	6"	C	7'-0"	21,300
UV2-5050	5'-0"	5'-0"	6"	6"	C	4'-0"	8,300
UV1-5106	5'-0"	10'-6"	6"	6"	T	4'-0"	11,563
UV1-5012	5'-0"	12'-0"	6"	6"	T	3'-8"	15,300

CATALOG NUMBER	W	L	T	B	CORE TYPE	H	WEIGHT
UV1-606D	6'-0"	6'-0"	6"	6"	C	3'-8"	10,500
UV1-608D	6'-0"	6'-0"	6"	6"	C	4'-0"	13,725
UV1-608D	6'-0"	6'-0"	6"	6"	C	7'-0"	20,475
UV1-609D	6'-0"	6'-0"	6"	-	-	2'-6"	5,000
UV1-6012	6'-0"	12'-0"	6"	6"	T	3'-8"	16,800
UV1-6126	6'-0"	12'-6"	6"	6"	C	7'-0"	27,563
UV1-6015	6'-0"	15'-0"	6"	6"	T	3'-8"	19,950
UV1-6018	6'-0"	18'-0"	6"	6"	T	3'-8"	30,251
UV1-7080	7'-0"	8'-0"	6"	6"	C	7'-0"	22,200
UV1-8016	8'-0"	16'-0"	6"	6"	C	3'-8"	33,911
UV1-1010	10'-0"	10'-0"	6"	6"	C	3'-8"	20,100
UV1-1112	11'-0"	12'-0"	6"	6"	T	5'-8"	40,337
UV1-1117	11'-0"	17'-0"	6"	6"	T	5'-8"	51,451
UV1-1119	11'-0"	19'-0"	6"	6"	T	5'-8"	55,897
UV1-1122	11'-0"	22'-0"	6"	6"	T	5'-8"	62,566
UV1-1124	11'-0"	24'-0"	6"	6"	T	5'-8"	67,012
UV1-1127	11'-0"	27'-0"	6"	6"	T	5'-8"	73,880
UV1-1129	11'-0"	29'-0"	6"	6"	T	5'-8"	78,126
UV1-1134	11'-0"	34'-0"	6"	6"	T	5'-8"	89,241