



1. Concrete: 28 Day Compressive Strength f'c = 4,500 psi.

- Conforms to all applicable NJ DOT specs.
 1" chamber on exposed edges.

| Specifications | | | | | | |
|----------------|----------|-----|-----|-----|--------------------|---------------|
| PIPE Ø | А | В | С | D | E | WEIGHT (lbs.) |
| 12" | 12"-19" | 30" | 48" | 74" | 109 3 " | 14,160 |
| 15" | 15"-24" | 30" | 48" | 74" | 109 <u>3</u> " | 13,980 |
| 18" | 18""–28" | 30" | 48" | 74" | 109 3 " | 13,820 |
| 21" | 21"-30" | 30" | 48" | 74" | 109 <u>3</u> " | 13,700 |
| 27" | 27"-36" | 48" | 72" | 78" | 151 3 " | 21,240 |
| 30" | 30"-42" | 48" | 72" | 84" | 151 <u>3</u> " | 22,780 |
| 36" | 36"-50" | 48" | 72" | 90" | 151 <u>3</u> " | 24,060 |
| 42" | 42"-56" | 48" | 96" | 90" | 175 <u>3</u> " | 29,100 |
| 48" | 48"-64" | 48" | 96" | 90" | 175 <u>3</u> " | 28,080 |

Mid Atlantic Region