

7/16" X 1'-10" X 5'-1" Protective Barrier Panels 3 Req'd

Steel Closure Plate
5'-6 1/4" x 10" x 1/4"

Identification Spot

30"Ø R.P.M. Cover With A1106 Frame and Gasket
Optional A1106 Traffic Cover Is Available

Recessed Lifting Pin

1 5/8" x 1 5/8" x 8'-10"
Flush Mount Unistruts
1 Ea. Side Wall
2 Total

60" x 61"
Clear Opening

30" Clear Manhole Opening

4 Ton Swiftlifts
2 Ea. Side Wall
4 in Base
8 Total

Top Section

* 6" Riser Available

5'-10"
4'-0"

11'-4"

1 5/8" x 1 5/8" x 8'-10"
Flush Mount Unistruts
1 Ea. Side Wall
2 Total

5/8"Ø x 10" Copper Clad
Ground Rods Grounded To Rebar
1 Ea. In Opposite Corners
2 Total

6"Ø Terminators
12 Ea. End Wall
24 Total

13"Ø Sump

CU-1600-3J
Overall Outside Dimensions
5'-10"W x 11'-4"L x 8'-0"H
Overall Inside Dimensions
5'-0"W x 10'-6"L x 7'-0"H
Minimum Excavation Is To Be
12" Larger Than Product On
All Sides

Approximate Weights
Top - 10,400 Lbs.
Bottom - 12,100 Lbs

SCALE: 3/16" = 1'-0"



Southern California
Fontana, San Diego, Santa Paula
Phone: 800-626-3860 Fax: 909-428-3737

ANAHEIM 5106-84PMH

FILE NAME: 070UEE5106PMHAN.DWG

REVISED: Dec. 2006

www.oldcastleprecast.com

5'-0" x 10'-6" x 7'-0"
PMH Vault
City of Anaheim

Copyright © 2008 Oldcastle Precast, Inc.