



Total Standard Necking
Parkway 30" – Traffic 24"

Identification Spot

A1134 Traffic Cover and Frame
A1136 Parkway Cover and Frame
Are Also Available

OPTIONAL
3" Riser
6" Riser
12" Riser

36" To 30" Reducer
Ring Available In
9" and 6" Heights

OPTIONAL
3" Riser
6" Riser
12" Riser

2'-6" or 2'-0"
End Section

5'-0" Access
Section

5'-0" Intermediate
Section

5'-0" Access
Section

2'-6" or 2'-0"
End Section

4'-0" Wide Intercept
Slot Through Floor
8'-0" x 5'-0" Wide
Slot Up End Walls

End Section – Bell	10'	14'	15'	19'	20'	29'	30'
Male End Wall (2'-0" Inside)		1		1		1	
Male End Wall (2'-6" Inside)	1		1		1		1
Access Section	1	2	2	2	2	2	2
Intermediate Section				1	1	3	3
Female End Wall (2'-0" Inside)		1		1		1	
Female End Wall (2'-6" Inside)	1		1		1		1

Approximate Weights
End Sections
2'-0" – 8300 Lbs
2'-6" – 10000 Lbs
Access – 10500 Lbs
Intermediate – 11100 Lbs

SCALE: 3/16" = 1'-0"

Overall Outside Dimensions
7'-0"W x 10'-1"H x Length Varies
Overall Inside Dimensions
6'-0"W x 9'-0"H x Length Varies
Minimum Excavation Is To Be
12" Larger Than Product On
All Sides

Oldcastle Precast
UTILITY VAULT™ Division
Southern California
Fontana, San Diego, Santa Paula
Phone: 800-626-3860 Fax: 909-428-3737

AT&T 69INTTUNNEL
FILE NAME: 070UTT69ITVTATT.DWG
ISSUE DATE: Feb. 2008
www.oldcastleprecast.com

**AT&T 6'-0" x 9'-0" x 19'-0"
Modular Manhole, Intercept**
Copyright © 2008 Oldcastle Precast, Inc.