
NOTES:

- 1. FOR FRAME SIZES SEE 'TYPICAL FRAME AND GRATE' PAGE.
- 2. 1/2" MAXIMUM SPACING BETWEEN BEARING BARS.

	AMERICAN	DISABILITIES ACT (ADA), WHEEL CHAIR PROOF PEDESTRIAN GRATES					
		GRATE SIZE		GRATE	WEIGHT	BEARING	
	SIZE	A	В	HEIGHT	(LBS)	BAR QTY.	
	12x12	14 5/8"	11 7/8"	1 1/4"	20	18	
	18x18	20 5/8"	18"	1"	32	26	
	18x24	20 5/8"	24"	1 1/4"	54	35	
	24x24	26 3/4"	24"	1 1/4"	68	35	
	24x30	26 3/4"	30"	1 1/4"	87	44	
2 PC.	24x36	26 1/2"	36"	1 1/4"	106	53	
2 PC.	24x48	26 5/8"	48"	1 1/4"	133	72	


AMERICAN DISAB	ILITIES ACT ((ADA), WHE	FI CHAIR PRO	OF TRAFFIC						
			AMERICAN DISABILITIES ACT (ADA), WHEEL CHAIR PROOF TRAFFIC GRATES							
	GRATE SIZE			WEIGHT	BEARING					
SIZE	4	В	HEIGHT	(LBS)	BAR QTY.					
	5/8" 11	7/8"	1 1/4"	20	18					
18x18 20 5	5/8"	18"	2 1/4"	72	26					
18x24 20 5	5/8"	24"	2 1/4"	87	35					
24x24 26	3/4"	24"	2 1/4"	122	35					
24x30 26 3	3/4"	30"	2 1/4"	156	44					
24x36 26	1/2"	36"	2 1/4"	191	53					
24x48 26 5	5/8"	48"	2 1/4"	236	72					



NOTES:

- 1. FOR FRAME SIZES SEE 'TYPICAL FRAME AND GRATE' PAGE.
- 2. 1/4" MAXIMUM SPACING BETWEEN BEARING BARS.
- 3. TRAFFIC RATED HEEL PROOF GRATES ARE AVAILABLE UPON REQUEST.

HEEL PROOF PEDESTRIAN GRATES								
	GRATE	SIZE	GRATE	WEIGHT	BEARING			
SIZE	А	В	HEIGHT	(LBS)	BAR QTY.			
12x12	14 5/8"	11 7/8"	1 1/4"	27	27			
18x18	20 5/8"	18"	1"	33	42			
24x24	26 3/4"	24"	1 1/4"	101	55			



NOTES:

- 1. GRATES ARE HOT-DIPPED GALVANIZED AFTER FABRICATION.
- 2. ADDITIONAL SIZES AVAILABLE UPON REQUEST
- 3. LOCKING BOLTS INCLUDED

DRAWING MAY NOT CONFORM TO THE MOST CURRENT SPECIFICATION



Madera ■ Morgan Hill ■ Pleasanton ■ Santa Rosa ■ Stockton ■ Tulare

Phone: 925-750-6650 Fax: 925-750-6660

ADA & HEEL GRATES

FILE NAME: SD-13.DWG

REVISED: MARCH 2016
www.oldcastleprecast.com

TYPICAL GRATES
DRAINAGE INLET
STORM DRAIN

Copyright © 2016 Oldcastle Precast, Inc.