




	LAY L	REINFORCED				
DIA.	8'	12'	ASTM C-76			
36"	_	536 #	II, III, IV, V			
42"	-	714 #	II, III, IV, V			
48"	_	1,012 #	II, III, IV, V			
54"	1,233 #	1,233 #	II, III, IV, V			
60"	1,470 #	1,470 #	II, III, IV, V			
66"	1,739 #	1,739	II, III, IV, V			
72"	2,024 #	2,024 #	II, III, IV, V			
84"	2,658 #	_	II, III, IV, V			
90"	3,009 #	_	II, III, IV, V			
96"	3,098 #	_	II, III, IV, V			



NOTES:
1. Pipe is also available in Low-Head Pressure pipe meeting ASTM C-361, up to 125 feet of head.
2. Pipe fittings are available.






STANDARD JOINT DETAIL

MODIFIED "BABY" BELL JOINT DETAIL
36" & 42" DIA. ONLY

DIA.	Α	B DIA.	С	D	E	F	G	H DIA.	J DIA.	K DIA.	Γ.	M*	N RAD.
36"	4.00	44.00	3.50	-	-	-	-	-	-	39.298	-	-	-
42"	4.50	51.00	4.25	0.337	1.0	1.0	0.75	46.137	45.614	45.567	10*	20°	0.125
48"	5.75	59.50	4.50	-	1.014	1.174	1.126	52.312	52.054	51.564	1.83*	30 <b>°</b>	0.625
54"	6.25	66.50	4.25	0.430	1.0	1.188	0.875	59.028	58.363	58.279	10°	20°	_
60"	6.75	73.50	4.75	0.430	1.0	1.188	0.875	65.175	64.510	64.426	10°	20°	_
66"	7.25	80.50	5.00	0.430	1.0	1.188	0.875	71.675	71.010	70.926	10°	20°	_
72"	7.75	87.50	5.00	0.547	1.0	1.250	0.875	79.250	78.585	78.270	10*	20°	0.25
84"	8.75	101.50	5.00	0.547	1.250	1.250	1.250	90.970	90.430	90.007	5 <b>°</b>	20°	_
90"	9.25	108.50	6.125	0.605	1.517	1.514	1.125	97.616	97.242	96.551	1*50'	30°	0.625
96"	9.00	114.00	6.25	0.605	1.517	1.514	1.125	104.041	103.667	102.976	1*50'	30°	0.625

DIA.	P RAD.	Q RAD.	R RAD.	S	T DIA.	As
36"	-	-	-	7.0	45.64	-
42"	0.25	0.25	0.375	6.25	52.36	0.058
48"	0.625	0.50	0.50	NA	NA	1
54"	_	-	_	NA	NA	0.094
60"	-	-	-	NA	NA	0.094
66"	_	-	_	NA	NA	0.094
72"	0.50	0.50	0.50	NA	NA	0.094
84"	_	-	_	NA	NA	0.094
90"	0.625	1.00	0.50	NA	NA	0.110
96"	0.625	1.00	0.50	NA	NA	0.110



36" & 42" MODIFIED "BABY" BELL

Oldcastle Precast 801 West 12th Street Ogden, Utah 84404 Phone: (801) 399-1171 Fax: (801) 392-7849

For more information about our products, please visit oldcastleprecast.com

oldcastleprecast.com