


Duralite®

3048



	А	В	С
3048-18	33 3/8"	50 7/8"	18"
3048-24	33 3/8"	50 7/8"	24"
3048-36	33 3/8"	50 7/8"	36"

Cover comes standard with permanent markings for manufacturer, load rating, model size and manufacturing location. Based upon lid and body combination, this unit can be Tier 15 or Tier 22. T22 rating when paired with T22 polymer concrete lid.

Revision 04/2023

oldcastleinfrastructure.com (888) 965-3227

Material & Style

Composite Straight Wall

3048-18

ANSI/SCTE-77, Tier 15 90 lbs

ANSI/SCTE-77, Tier 22 90 lbs

3048-24

ANSI/SCTE-77, Tier 15 112 lbs

ANSI/SCTE-77, Tier 22 112 lbs

3048-36

ANSI/SCTE-77, Tier 15 147 lbs

ANSI/SCTE-77, Tier 22 147 lbs

Options

Mouseholes/Knockouts



Medium Duty ANSI/SCTE TIER 15



ANSI/SCTE TIER 15




Heavy Duty ANSI/SCTE TIER 22

For use in non-vehicular traffic situations only. Weights and dimensions may vary slightly. Actual load rating is determined by the box and cover combination.

Trusted partnerships. Full scale solutions.







Raw Material	BODY : Material Property	Test Method	Typical Value ¹
Specification	Density	ASTM D1505	0.960 to 0.980, g/cm3
	Tensile Strength, at break	ASTM D638	5,500 to 7,700 psi
	Flexural Modulus	ASTM D790	400,000 to 500,000 psi
	Impact Resistance	ASTM D5420	60.0 in-lb

¹ The values listed for physical property measurements are nominal values only. Certain physical property measurements are subject to variations consistent with the test methods and are within a generally accepted range for such values.



Product modifications, including but not limited to, cutting for conduit access, or "mouseholes" may alter ratings and product performance listed within this document unless stated otherwise.

All information contained on this sheet is current at the time of publication. Oldcastle reserves the right to discontinue or update product information without notice.

© 2023 Oldcastle Infrastructure, Inc.