



**MATERIAL & STYLE**

Polymer Concrete  
Flush Split Cover  
Non-skid texture

**HARDWARE**

1/2-13 Stainless Steel Hex  
Head Bolt, Washer and  
Floating Nut

**PERFORMANCE &  
WEIGHT**

ANSI/SCTE-77, Tier 22  
337 lbs / Half

**OPTIONS**

- Marking Plate
- Hex Head Bolt
- Penta Head Bolt
- Penta Head Coil Thread Bolt
- Vandal Resistant Bolt
- Logos and Special Markings
- EMS Marker

Cover comes standard with permanent markings for manufacturer, load rating, model size and manufacturing location.

**RAW MATERIAL SPECIFICATION**

COVER : Material Property	Test Method	Typical Value <sup>1</sup>
COMPRESSIVE STRENGTH	ASTM C 579	> 12,500 PSI
FLEXURAL STRENGTH	ASTM D 790	> 3,000 PSI
MODULAS OF RUPTURE	ASTM C 99	≥ 3,000 PSI
WATER ABSORPTION	ASTM C 97	≤ 0.25%
IMPACT RESISTANCE	ASTM D 2444	> 70 FT-LB
FRICTION COEFFICIENT	ASTM C 1028	> 0.5
CHEMICAL RESISTANCE	ASTM D 543	RESISTANT, > 75% RETENTION PHYSICAL PROPERTIES

<sup>1</sup> The values listed for physical property measurements are nominal values only. Certain physical property measurements are subject to variations consistent with the test methods and are within a generally accepted range for such values.

**⚠ WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

All information contained on this sheet is current at the time of publication.  
Oldcastle reserves the right to discontinue or update product information without notice.

Revision 04/19/21



**HEAVY DUTY**  
ANSI/SCTE TIER 22

For use in non-vehicular traffic situations only. Weights and dimensions may vary slightly. Actual load rating is determined by the box and cover combination.

© 2021 Oldcastle Infrastructure, Inc