



## Underground Enclosures Non-deliberate traffic

### Material

Concrete with Reinforced Ring and Cover

### Load Rating:

ANSI/SCTE 77 - 3K

### Application:

Light duty pedestrian traffic only



Model	Size (LxW)	Shape	Depths	Performance
F08	8" Dia	Round	12"	ANSI/SCTE 77 Non-deliberate Traffic  Light Duty / Pedestrian Traffic
B03	9" x 14"	Rectangle	12"	
B09/N09	10" x 15"		12", [24]", [36]"	
B12	12" x 18"		12", [24]", [36]"	
B16 / N16	11" x 21"		12", [24]", [36]"	
B65	15" x 27"		12", [24]", [36]"	
B24	18" x 19"		12", [24]", [36]"	
B30 / N30	13" x 24"		12", [24]", [36]"	
B36 / N36	17" x 30"		12", [24]", [36]"	
N40	24" x 36"		12", [24]", [36]"	
N48	30" X 48"		12", [24]", [36]"	
N52	30" x 60"		12", [24]", [36]"	

Dimensions may vary slightly.

KEY: [#] Requires an extension unit. Maximum stackable depth is 36".

Please consult the Christy Enclosures engineering team if your project requires a depth greater than 36".



## Underground Enclosures Deliberate traffic

### Material

Concrete with Steel Frame and Reinforced Steel Cover

*Rectangle covers are available in galvanized or black painted.*

*Round covers are available in multiple colors, please consult customer service.*



### Load Rating:

AASHTO HS20-44

### Application:

Roadways  
Deliberate traffic.

Model	Size (LxW)	Shape	Depths	Performance
G03	10" Dia	Round	12"	AASHTO HS20-44 Deliberate Traffic
G04	11" Tri		12"	
G05	11" Dia		12", [24]", [36]"	
G08	11" Dia		12", [24]", [36]"	
G12	13" Dia		12"	
B1017	10" x 17"	Rectangle	12", [24]", [36]"	
B1324	13" x 24"		12", [24]", [36]"	
B1730	17" x 30"		12", [24]", [36]"	
B2436	24" x 36"		12", [24]", [36]"	
B3048	30" x 48"		12", [24]", [36]"	

Dimensions may vary slightly.

KEY: [#] Requires an extension unit. Maximum stackable depth is 36".

Please consult the Christy Enclosures engineering team if your project requires a depth greater than 36".

Trusted partnerships.  
Full scale solutions.

