

Solutions for Large Water Meters

Oldcastle Infrastructure offers innovative and reliable product solutions for customers installing and maintaining vaults for large water meters. Our extensive range of solutions is designed to meet the diverse needs of water management projects across North America. We deliver products that not only meet industry standards but also exceed expectations. Our vault solutions have faster lead times than other options, are easier to deliver, install and modify in the field, and have options and accessories that integrate seamlessly for a complete solution.




Oldcastle FRP

- ANSI Tier 15, Non-deliberate traffic
- Models from 30" x 48" to 48" x 96"
- Depths up to 48"
- · Rectangular or Round
- · Flared and straight wall options
- · Accessories available*



Duralite®

- · ANSI Tier 22, Non-deliberate traffic
- Models from 30" x 48" to 36" x 60"
- Depths up to 48"
- Rectangular options
- Straight walls
- · Accessories available*



STAKKAbox™ ULTIMA Connect

- 32,000 lb load rating
- Deliberate traffic
- Standardized components
- · Customize length, width and depth
- Ship flat
- Assembles around infrastructure no service shut-offs
- Accessories available*

^{*}A variety of accessories are available to customize the vault for your site-specific needs. From mounting options for AMI end points to ladders and marking plates, please reach out to your local Sales Representative for more details

Solutions for Large Water Meters

Non-deliberate traffic applications:

Oldcastle FRP enclosures and Duralite® enclosures.

Brand	Model	Available Depths	Performance Load Rating	
Oldcastle FRP	3048	30" / 36"	ANSI Tier 15 – Applications subject to occasional non-deliberate heavy vehicular traffic. Design load 15,000 lbs and a minimum failure load of 22,500 lbs.	
	3060	30" / 36"		
	3660	30" / 36"		
	4872	36" / 48"		
	4896	36" / 48"		
Duralite®	3048	36"	ANSI Tier 22 – Applications subject to occasional non-deliberate heavy vehicular traffic. Design load 22,500 lbs and a	
	3660	36"	minimum failure load of 33,750 lbs.	

Deliberate traffic applications:

STAKKAbox™ ULTIMA Connect chamber access system.

Brand	Vault Width	Vault Length	Vault Depth	Performance
	(min/max)	(min/max)	(min/max)	Load Rating
STAKKAbox™ ULTIMA Connect	18" / 96"	18" / no max	12" / no max	32,000lb Load Rating

CONTACT US TODAY:

For more information on any of these products, please call your local Sales Representative or call Oldcastle Infrastructure directly at (888) 965-3227.



Trusted partnerships. Full scale solutions.

